

DIRECTIONS:

Be sure that powder has completely dissolved before running through equipment.

High Pressure & Automatic Vehicle Wash:
Mix 1/2 to 1 oz of product per gallon of water or 2-3 lbs per 100 gallons of water.

Manual Applications: Use 1-2 oz per gallon of water.

Vehicle should be wet and cool prior to application. Foam solution onto surface. Agitate if needed with a soft brush. Allow 2-5 minutes of contact time. Do NOT allow solution to dry on surface. Rinse thoroughly with water.

DETCO

8543

High Sudsing Vehicle Washing Compound

WARNING

KEEP OUT OF REACH OF CHILDREN
Net Contents: 50 lbs (22.68 kg)

Detco 8543 is a high foaming washing compound designed to clean cars, trucks and equipment by hand, pressure washer or automatic wash system. It can be used as a bug prep, brush lube or detergent. It is safe on aluminum, chrome glass, paint and all other automotive surfaces when used as directed.

WARNING

Causes skin irritation. Causes serious eye irritation.
Wash hands thoroughly after handling. Wear protective gloves/eye protection.
IF ON SKIN: Wash with plenty of soap and water. **IF skin irritation occurs, get medical advice/attention. IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

INGREDIENTS (CAS#): STPP (7758-29-4), Sodium Bicarbonate (144-55-8), Sodium Carbonate (497-19-8), Nonylphenol Ethoxylate (9016-45-9), DBSA (68081-81-2).



0531-050



Detco Industries, Inc.
Conway, AR
1-800-282-2133
www.detco.com