



Our Vision . . . a Safe Environment!!

Code Clear

Clear RTV Silicone

Sealant • Caulk • Adhesive • Gasket Maker
Seals, Bonds, Insulates

Low Volatile • Easy to Use
Economical • Eliminates Waste
Waterproof • Weatherproof • Flexible
Eliminates Squeeze Tubes & Cartridge Guns

- 100% R.T.V. Silicone - Industrial Strength
- Pressurized dispenser enables easy application
- Remains permanently flexible at temperatures from -60°F to +500°F
- Caulks around tubs, sinks, showers and plumbing fixtures
- Seals around widows, doors, tile, marble, etc.
- Bonds most materials, similar or dissimilar (glass, wood, metal, porcelain, rubber, plastic, marble, ceramics, etc.)

NET WT. 8 OZ. (227 G.)

CAUTION: CONTACT WITH UNCURED SEALANT CAUSES IRRITATION. CONTENTS UNDER PRESSURE OUTER CONTAINER IS PRESSURIZED WITH A FLAMMABLE HYDROCARBON PROPELLANT. DO NOT REMOVE RUBBER PLUG IN BOTTOM OF CONTAINER.

SEE OTHER CAUTIONS ON BACK PANEL.

KEEP OUT OF REACH OF CHILDREN.

TO REORDER CALL:

1-800-282-2133



1375 Thomas G. Wilson Dr.
Conway, AR 72032
(800) 282-2133

This R.T.V. Silicone Caulk and Sealant is ideal for use wherever a strong permanently elastic weatherproof caulk, sealant or adhesive is needed. Designed to seal non-porous surfaces around ceramic tile, cultured marble, showers, tubs, sinks and plumbing fixtures. Ideal for caulking windows, doors, sills and ceiling cracks and crevices.

Features excellent adhesion and high chemical resistance. Will not sag or shrink during severe temperature changes. Useful for sealing cracks in machinery, heating and ventilation duct work, plumbing fixtures, electrical connections and low pressure water and drain lines.

Bonds nameplates, machinery flanges, glass, signs, electrical insulation etc. Offers unmatched performance under the most severe conditions. Remains flexible and will not shrink, crack, crumble or dry out.

NOTE: Paint will not adhere to cured material. Not recommended for continuous immersion in water or application to porous surfaces such as masonry.

DIRECTIONS:

Read Material Safety Data Sheet before using.

1. Surface must be clean, dry and free of oil, tar, dirt and dust for best adhesion.
2. Hold can at 45° angle and apply a continuous bead of 1/16" to 1/8" to the mating surfaces.
3. Starts to cure immediately, fully cures in 24 hours and reaches optimum strength in 7 days.

This product has been designed to meet the qualifications of Federal Specification TT-S-001543, Class A; TT-S-00230, Class A; ASTM C 920; MIL-A-46106A, Type1; Canadian Specification CGSB 19-GP-22M; FDA Regulation No. 21 CFR 177.2600; and National Sanitation Foundation RatingmC2.

CAUTION: CONTACT WITH UNCURED SEALANT CAUSES IRRITATION. OUTER CONTAINER IS PRESSURIZED WITH A FLAMMABLE HYDROCARBON PROPELLANT. DO NOT REMOVE RUBBER PLUG IN BOTTOM OF CONTAINER.

Use with adequate ventilation. Product releases acetic acid (vinegar-like odor) during curing. Contact lens wearers take appropriate precautions. Contents under pressure. Do not puncture or incinerate. Do not store at temperatures above 120°F (50°C). Do not store in automobiles, in direct sunlight or any area with temperatures above 120°F.

FIRST AID:

IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. Seek medical attention immediately. **IF SKIN CONTACT:** Wipe off excess sealant with dry paper towel or cloth, and wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. No additional first aid should be needed.

CONTAINS: Amorphous Silica (CAS#7631-86-9), Methyltriacetoxysilane (CAS# 4253-34-3), Ethyltriacetoxysilane (CAS# 17689-77-9) and Liquefied Petroleum Gas (68476-85-7).

HMIS RATING: Health, 1; Flammability, 1; Reactivity, 0; Personal Protection, B.



After each use, leave a small bead of material, which will form a sealing "plug" for reuse. To use, gently pull "plug" and begin to use material. If plug breaks, leaving the dispensing tip sealed, use a paper clip or other wire object to remove and loosen the remainder of the cured material.

NOTE: Color proofs are provided ONLY as a visual reference to the final piece. The colors shown are ONLY representational and are not intended to match the actual press or silk screening colors.	customer / product no. 1003957-11707	FINISHING <input type="checkbox"/> One Color Silk Screen <input type="checkbox"/> Two Color Silk Screen <input type="checkbox"/> Paper Label <input type="checkbox"/> Litho-Like Label <input type="checkbox"/> Lithograph Can <input type="checkbox"/> Process <input type="checkbox"/> Spot	LABEL PROOF APPROVAL Your Approval of This Label is Our Authority to Proceed. CPC WILL NOT PROCEED WITHOUT A SIGNED APPROVAL.
	FINISHING CODE 0-99-0		
	original: 05-11-07 revision: _____ art by: _____		Signature _____ Date _____