

DIRECTIONS:

Degreasing: Dilute 2-4 oz per gallon of water. Spray or foam onto surface. Allow 2-3 minutes of contact time. Do NOT allow product to dry on surface. Rinse with clear water.

Bug Removal: Dilute 40:1 with water. Spray onto surface and allow 1-3 minutes of contact time. Do NOT allow product to dry on surface. Proceed with normal truck washing procedure.

PRESOAK

Non-Phosphate High Foaming Alkaline Detergent

WARNING
KEEP OUT OF REACH OF CHILDREN
Net Contents: 5 gal (18.93 L)

Presoak is a highly concentrated, non-phosphate alkaline detergent for use in manual or automatic car wash systems. It removes bugs and road film.



Detco Industries, Inc.
Conway, AR
1-800-282-2133
www.detco.com

WARNING
Causes skin irritation. Causes serious eye irritation.
Wash hands thoroughly after handling. Wear protective gloves/eye protection.
IF ON SKIN: Wash with plenty of soap and water. **IF skin irritation occurs, get medical advice/attention. IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **IF eye irritation persists, get medical advice/attention.**

INGREDIENTS (CAS#): Water (7732-18-5), Tetrasodium EDTA (64-02-8), Sodium Metasilicate (6834-92-0), Surfactant (68439-46-3).



1390-005



0