

**DIRECTIONS:**  
Vacuum area to be cleaned to remove loose dirt, lint and other materials. Mix Down Under at the rate of 2 oz per gallon of water for light cleaning and 6 oz per gallon of water for heavy cleaning. Mix in the hot water tank of the extractor. Operate extractor unit according to manufacturer's instructions, then allow to air dry.

# DOWN UNDER

## Carpet Shampoo

### WARNING

Flammable liquid and vapour.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Wear protective gloves/protective clothing/eye protection/face protection.  
IF ON SKIN.(or hair) Take off contaminated clothing. Rinse skin with water/show-  
er. Store in a well-ventilated place.  
Keep cool. Dispose of contents/con-  
tainer in accordance with federal,  
state and local regulations.

For Use in  
Carpet Extractors

### WARNING

KEEP OUT OF REACH OF CHILDREN  
Net Contents: 1 gal(3.79 L)



0591-001



**Down Under** is a low-foaming shampoo for use in carpet extraction machines. It removes tough stains and prevents them from redepositing on the surface of the carpet. May be used on all color fast fibers, acrylic, nylon, polyester, rayon and wool.

**Detco Industries, Inc.**  
Conway, AR  
1-800-282-2133  
[www.detco.com](http://www.detco.com)

**Detco**

0 21855 05916 6



INGREDIENTS (CAS#): Water (7732-18-5),  
Isopropanol (67-63-0), TKPP (7320-34-5),  
Diisopropylene Glycol Methyl Ether (34590-34-8),  
Surfactants.