

#494405

#13393

09/17

4 cp



D L494405DETCO-P20

This powerful combination of concentrated solvents is specially formulated to remove dirt, gum and varnish deposits that tend to build up on the moving and sealing surfaces of engine carburetors, heat valves and automatic chokes, throttle bodies, PCV valves and linkages. Our product helps to free sticky valves, stuck heat risers and throttle linkages. No lead or silicone. Will not harm oxygen sensors, catalytic converters or fuel injectors. Periodic use on cars, trucks, boats, lawnmowers, etc., will keep engines clean, fuel efficient and trouble free. This product is formulated for high performance without the use of ozone depleting chlorinated solvents.

DIRECTIONS:

FOR GASOLINE ENGINES ONLY
Always hold can in an upright position during use. Remove cap and insert extension tube into spray tip.

CARBURETOR: Turn engine off and remove the air cleaner assembly. Spray small amount into carburetor throat walls and outside surfaces. Spray small amount into float chamber through float chamber vent. Start engine and run at fast idle for 60 seconds, then stop engine. Spray all linkages, bowls, chambers, floats, jets and setting screws. Deposits will dissolve and flush away. **CHOKE:** Turn engine off. While opening and closing choke by hand, spray both ends of valve shaft. **PCV VALVE:** Turn engine off. After disconnecting valve hose, spray cleaner directly into PCV valve. Start engine, run for one or two minutes then shut engine off. Spray valve once more and reconnect hose. **HEAT VALVE:** Turn engine off. Spray cleaner into open end of valve shaft. After allowing spray to penetrate, move valve up and down. Repeat until valve moves freely. **OTHER USES:** Frees heat risers by dissolving build up around shaft. **IMPORTANT:** Do not spray or spill on painted surfaces.

PRECAUTIONARY STATEMENT:

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Wear eye protection/face protection. Do not handle until all safety precautions have been read and understood. Avoid release to the environment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. **IF SWALLOWED:** Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. **IF ON SKIN:** Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing, and wash it before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Collect spillage. Protect from sunlight. Store in a well-ventilated place. Store locked up. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents and container in accordance with all local, regional, national and international regulations.

NOT AVAILABLE FOR SALE IN CALIFORNIA. OTHER LOCALES MAY ALSO PROHIBIT ITS SALE OR USE. CHECK LOCAL AND STATE REGULATIONS.

09/17

CONTAINS (CAS#): Acetone (67-64-1), Propane (74-98-6), Toluene (108-88-3), Xylene (1330-20-7), Ethylbenzene (100-41-4).

VOC Content 45%



DISTRIBUTED BY:
DETCO INDUSTRIES, INC.
PO BOX 430 CONWAY, ARKANSAS 72033
1-800-282-2133 or 1-501-329-6965
www.detco.com



AUTO CHOKE & CARB CLEANER



- FOR GASOLINE ENGINES ONLY
- High Pressure Blast Spray
- Dissolves Carbon, Gum and Varnish
- No Chlorinated Solvents
- No Ozone Depleters
- Eliminates Stalling and Rough Idling



DANGER:

EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. MAY CAUSE DROWSINESS OR DIZZINESS. MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. VERY TOXIC TO AQUATIC LIFE. Read rear panel for additional precautions.

NET WT. 12 OZ. (340 grams)