

ANTI-LOCK is a copper-based anti-seize lubricant formulated to withstand high temperatures and extreme pressures. Continues ground conductivity better than ordinary lubricants. Imbedded with copper to improve conductivity. Seals out moisture, gases and corrosive fluids from threaded connections. Contains rust and corrosion inhibitors to assure long life of connectors.

USES: All threaded fittings, hand and motor operated valves, gaskets, flanges and "O" rings, bushings, bearings, rollers and conveyors, gears, transmission boxes, chains and drives, electric motors, compressors, hoists, turbines and winches, furnaces, burner assemblies, regulators, pumps, valve stems, control chests and headers, man and handheld and inspection doors, cylinder head, manifold and stud assemblies, fuel injectors, pre-combustion chambers, valve cages, turbo-charger fittings, guides and thread tubing, keyways and spark plugs, torque rod pins and tubes, air cylinder assemblies, pneumatic cylinder shafts, air slides and axle shafts.

DIRECTIONS:

Shake can well before using. Clean surface thoroughly. Apply only enough to form a solid film over contact surfaces of threads, gaskets, bushings, etc. Assemble and wipe off excess.

MODO DE EMPLEO:

Agite bien antes de usar. Limpie bien la superficie. Aplique solo lo necesario para formar una capa pequeña sobre la superficie de contacto de la rosca, juntas conexiones, etc. Ensamble y limpie el exceso.

DANGER:

FLAMMABLE. Contents under pressure. Contains petroleum distillates. Do not puncture or incinerate container. Do not use or store near heat or open flame. Exposure to temperatures above 120°F may cause bursting.

PELIGRO:

INFLAMABLE. Contenido bajo presión. Contiene destilados de petróleo. No pinche o incinere el contenedor. No use o almacene cercas del calor o llama abierta. Exposición a temperaturas por encima a 120°F puede causar explosión.

CONTAINS (CAS#): Polybutene (9003-29-6), Heptane (142-82-5), Copper (7440-50-8), Acetone (67-64-1), Propane/n-Butane (68476-86-8).

Made in USA

HMIS CODE:

0=MINIMAL 1=SLIGHT
2=MODERATE 3=SERIOUS 4=SEVERE

PERSONAL PROTECTION INDEX:
SAFETY GLASSES & GLOVES

HEALTH	1
FLAMMABILITY	3
REACTIVITY	1
PERSONAL	B

DISTRIBUTED BY:



PO BOX 430 CONWAY, AR 72033 • 1-800-282-2133 or 1-501-329-6965

ANTI-LOCK

COPPER-BASED ANTI-SEIZE

ANTI AGARROTAMIENTO A BASE DE COBRE



Reduces Seizing

Temperature Range -20°F to +1800°F

Imbedded with Copper to Improve Conductivity

50 State VOC Compliant



DANGER/PELIGRO:
FLAMMABLE. CONTENTS UNDER PRESSURE
KEEP OUT OF REACH OF CHILDREN
See Additional Cautions on Back Panel
INFLAMMABLE. CONTENIDO BAJO PRESIÓN
NO SE DEJE AL ALCANCE DE LOS NIÑOS
Vea Precauciones Adicionales en el Panel Trasero

NET WT. 12 OZ. (340 g)